

## Ambient 5% Openness/PVC Free


### Solar Screen




White




White/Beige




White/Gray



Gray/Gray



Charcoal/Gray



Charcoal/Charcoal

## Specifications

<b>Composition</b>	100% Polyester
<b>Openness</b>	5%
<b>Width(s)</b>	118" (3m)
<b>Length</b>	27yd/roll (30m)
<b>Weight</b>	9.38oz/yd <sup>2</sup> (318g/m <sup>2</sup> )
<b>Thickness</b>	0.021in (.53mm)
<b>Fire Classification</b>	NFPA-701, CA Title 19
<b>Railroadable</b>	Yes
<b>Cleaning</b>	Lightly vacuum to remove surface dust.

### Applications



PANEL



ROLLER

### Features



5 YEAR WARRANTY



ENERGY SAVING



FRAGRANCE FREE



PVC FREE



SCREEN

### Certifications



PHTHALATE FREE



FR



LEAD FREE



HEALTH PRODUCT DECLARATION



FORMALDEHYDE FREE



HMI Compliant



LBC Compliant



# AMBIENT

## PVC FREE SCREEN

### SPECIFICATIONS

	5%
Series	Ambient
Composition	100% Polyester
Openness Factor	Average 5%
Weight	9.38oz/yd <sup>2</sup> (318 g/m <sup>2</sup> )
Thickness	0.02in (.53mm)
Colorfastness	Grade 8
Average length	27 yd/roll (25m)
Width	118" (3m)
Cutting	Cold, Crush, and Ultrasonic
Railroadable	Yes
Cleaning	Wipe clean with warm soapy water and damp cloth.
Environmental Standards	Formaldehyde Free, PVC Free, Health Product Declaration, HHI Compliant, and LBC Red List Compliant
Fire Classifications	NFPA 701 and CA Title 19

### THERMAL AND OPTICAL FACTORS

CODE	Thermal Factors			Optical Factors	
	Ts	Rs	As	Tv	Tuv
WHITE/WHITE	32	63	5	33	12.4
WHITE/BEIGE	26	60	14	25	10.5
WHITE/GRAY	22	55	23	22	10

